

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1919M0505W |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-080-0606 |
| Schedule B: | 7508.90.5000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1919M05-05W Specifications

| | |
|--|--|
| Fastener Length: | 0.451 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Shear Strength: | 1565 Single Pounds Per Square Inch |
| Special Features: | Self-locking |
| Material: | Nickel Alloy 400 Body |
| Material: | Nickel Alloy 400 Sleeve |
| Material Document And Classification: | Qq-n-281 Form 7 Fed Spec Single Material Response Body |
| Material Document And Classification: | Qq-n-281 Form 7 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Cadmium Body And Chromate Body |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Specification/standard Data: | 80205-nas1919 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M05-05W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.