

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1919M0505W
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-080-0606
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1919M05-05W Specifications

<b>Fastener Length:</b>	0.451 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Shear Strength:</b>	1565 Single Pounds Per Square Inch
<b>Special Features:</b>	Self-locking
<b>Material:</b>	Nickel Alloy 400 Body
<b>Material:</b>	Nickel Alloy 400 Sleeve
<b>Material Document And Classification:</b>	Qq-n-281 Form 7 Fed Spec Single Material Response Body
<b>Material Document And Classification:</b>	Qq-n-281 Form 7 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Body And Chromate Body
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Specification/standard Data:</b>	80205-nas1919 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M05-05W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.