

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1919M0507
Minimum Qty (MOQ):	5
NSN:	5320-00-880-5871
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1919M05-07 Specifications

Fastener Length:	0.555 Inches Minimum And 0.575 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.375 Inches Minimum And 0.438 Inches Maximum
Shear Strength:	1565 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec 1st Treatment Response Sleeve Or Nas 4006 Assn Std 2nd Treatment Response Sleeve
Specification/standard Data:	80205-nas1919 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M05-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.