

**Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1919M0507                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5320-00-880-5871                            |
| Schedule B:             | 7508.90.5000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE  
AVAILABLE

## P/N NAS1919M05-07 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.555 Inches Minimum And 0.575 Inches Maximum  |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.067 Inches Minimum And 0.077 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.155 Inches Minimum And 0.159 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.296 Inches Minimum And 0.328 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.375 Inches Minimum And 0.438 Inches Maximum  |
| <b>Shear Strength:</b>                                | 1565 Single Pounds Per Square Inch   |
| <b>Material:</b>                                      | Iron Alloy 660 Stem  |
| <b>Material:</b>                                      | Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve   |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Stem  |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec All Material Responses Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve  |
| <b>Surface Treatment:</b>                             | Passivate Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 3 Fed Spec 1st Treatment Response Sleeve Or Nas 4006 Assn Std 2nd Treatment Response Sleeve |
| <b>Specification/standard Data:</b>                   | 80205-nas1919 Professional/industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1919M05-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.