

Description

5320-00-165-2085 NAS1921B06-03

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921B0603
Minimum Qty (MOQ):	10
NSN:	5320-00-165-2085
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



NO IMAGE
AVAILABLE

P/N NAS1921B06-03 Specifications

Fastener Length:	0.350 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.189 Inches Minimum And 0.193 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Self-locking
Material:	Aluminum Alloy 2024 Stem
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921B06-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.