

Description

Fastener Length: 1-29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921B06S10
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-180-7171
Schedule B:	7616.10.3000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1921B06S10 Specifications

<b>Fastener Length:</b>	1.446 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.563 Inches Minimum And 0.625 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2024 Stem
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec All Material Responses Overall
<b>Surface Treatment:</b>	Anodize Stem Or Oxide Film Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1921 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921B06S10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.