

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921B06S12
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-369-5759
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS1921B06S12 Specifications

Fastener Length:	0.912 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Single Acion,non-shifting Installation Tools,color Code Yellow On Spindle
Material:	Aluminum Alloy 5056 Locking Ringaluminum Alloy 5056 Sleevealuminum Alloy 2024 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ringqq-a-430 Fed Spec Single Material Response Sleeveqq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921B06S12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.