

Description

Fastener Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921C04S03
Minimum Qty (MOQ):	10
NSN:	5320-01-478-6259
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1921C04S03 Specifications

Fastener Length:	0.323 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Apache Attack Helicopter, Ah64
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Bulbed; 100% Flush Head; Mechanically-locked-spindle; Use W/single Action Tooling; Yellow Color Code On Spindle
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Specification/standard Data:	80205-nas1921 Professional/Industrial Association Standard

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.