

**Description**

Fastener Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1921C04S03
Minimum Qty (MOQ):	10
NSN:	5320-01-478-6259
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



## P/N NAS1921C04S03 Specifications

<b>Fastener Length:</b>	0.323 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Apache Attack Helicopter, Ah64
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	Bulbed; 100% Flush Head; Mechanically-locked-spindle; Use W/single Action Tooling; Yellow Color Code On Spindle
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Specification/standard Data:</b>	80205-nas1921 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.