

## P/N NAS1921C04S03U

### **Description**

NAS1921C04S03U Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1921C04S03U

Minimum Qty (MOQ): 10

NSN: 5320-01-528-3868

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1921C04S03U Specifications

Fastener Length:	0.323 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 316 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Locking Ring Or Ams 5690 Assn Std Single Material Response Locking Ring
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve Or Aluminum Alloy Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve Or Qq-p-416, Type Ii, Cl 3 Fed Spec Single Treatment Response Sleeve Or Nas 4006 Assn Std Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03U">https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03U">https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03U">https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S03U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1921C04S03U">https://military-fasteners.com/rivets/NAS1921C04S03U</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1921C04S03U">https://military-fasteners.com/rivets/NAS1921C04S03U</a> and selecting the property of the prope