

Description

NAS1921C04S04 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1921C04S04 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-475-9774 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N NAS1921C04S04 Specifications

| | |
|--|--|
| Fastener Length: | 0.398 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.225 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Locking Ring |
| Surface Treatment: | Passivate Sleeve Or Cadmium Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C04S04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.