

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921C0505W
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-012-4580
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1921C05-05W Specifications

Fastener Length:	0.451 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Sleeve
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416 Ty 2 Cl 3 Fed Spec 2nd Treatment Response Sleeve Or Nas 4006 Assn Std 3rd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C05-05W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.