

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921C05S04U
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-476-4784
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1921C05S04U Specifications

Fastener Length:	0.398 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	F16aircombf1t; F-16 Aircraft
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 316 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams5737 Assn Std Single Material Response Locking Ring Or Ams5690 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams5737 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve Or Qq-p-416, Ty li, Cl3 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S04U> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.