

P/N NAS1921C05S05U

Description

Length: 0.461", flat head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1921C05S05U

Minimum Qty (MOQ):

NSN: 5320-01-541-0463

Schedule B: 7318.23.0000

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS1921C05S05U Specifications

| Fastener Length: | 0.461 Inches Maximum |
|-------------------|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Material: | Iron Alloy 660 Locking Ring |

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S05U and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S05U and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S05U and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/NAS1921C05S05U and selecting the quantity you want https://military-fasteners.com/rivets/NAS1921C05S05U and selecting the quantity you want https://military-fasteners.com/rivets/NAS1921C05S05U and selecting the quantity you want https://military-fasteners.com/rivets/NAS1921C05S05U and selecting the property of the property