

## P/N NAS1921C05S06U

### **Description**

Rivet part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1921C05S06U

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-541-0467

Schedule B: 7318.23.0000

ECCN: EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1921C05S06U Specifications

Fastener Length:	0.523 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Iron Alloy 660 Locking Ring

## **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S06U">https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S06U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S06U">https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S06U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S06U">https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S06U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1921C05S06U">https://military-fasteners.com/rivets/NAS1921C05S06U</a> and selecting the quantity you want then