

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921C05S08
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-369-5768
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1921C05S08 Specifications

Fastener Length:	0.648 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Single Action,non-shifting Installation Tools,color Code Yellow On Spindle
Material:	Iron Alloy 660 Overall
Material Document And Classification:	As 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1921 Professional/Industrial Association Standard

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.