

**Description**

NAS1921C05S09U Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921C05S09U
Minimum Qty (MOQ):	25
NSN:	5320-01-544-6554
Schedule B:	7318.23.0000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1921C05S09U Specifications

<b>Fastener Length:</b>	0.711 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Rq-4a
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	"u"designates Rivet Utilizing Drive Anvil Washer As Part Of Rivet Assembly; Washer Allows Use Of Blunt Nosed Installation Tooling
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C05S09U> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.