

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1921C06S03                               |
| Minimum Qty (MOQ):      | 10 EA                                       |
| NSN:                    | 5320-01-534-3572                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1921C06S03 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.350 Inches Maximum   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.190 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.349 Inches Minimum And 0.357 Inches Maximum                                  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>End Item Identification:</b>                       | Helicopter Uh-tiger  |
| <b>Grip Length:</b>                                   | 0.126 Inches Minimum And 0.187 Inches Maximum                                  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                 |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams5737 Assn Std Single Material Response Overall                              |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Locking Ring                        |
| <b>Specification/standard Data:</b>                   | 80205-nas1921 Professional/Industrial Association Standard                     |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921C06S03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.