

Description

Fastener Length: 3/8", NAS1921 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M0404W
Minimum Qty (MOQ):	20
NSN:	5320-00-937-4984
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



P/N NAS1921M04-04W Specifications

Fastener Length:	0.385 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.228 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	1020 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Locking Ring Or Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material Document And Classification:	Ams 5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring Or Qq-n-281 Fed Spec 3rd Material Response Locking Ring
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 For A286 Cres Only Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Sleeve Or Nas 4006 Assn Std 2nd Treatment Response Sleeve
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M04-04W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.