

**Description**

Size: 1/8", grip range: 1/16" - 1/8", blind rivet (huck), flush head, bulbed, general purpose, monel, for use with single action installation tool

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1921M04S02                               |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-01-406-7890                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N NAS1921M04S02 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.260 Inches Maximum   |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.124 Inches Minimum And 0.128 Inches Maximum                                  |
| <b>Shank Style:</b>         | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b> | 0.229 Inches Maximum   |
| <b>Expansion Device:</b>    | Serrated Stem-type W   |
| <b>Grip Length:</b>         | 0.063 Inches Minimum And 0.125 Inches Maximum                                  |
| <b>Countersink Angle:</b>   | 100.0 Degrees Nominal  |
| <b>Material:</b>            | Iron Alloy 660 Stem  |
| <b>Material:</b>            | Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve                           |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.