

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M04S02AU
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-529-1377
Schedule B:	7508.90.5000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1921M04S02AU Specifications

Fastener Length:	0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Nh90, Helicopter
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet Blind, General Purpose, Bulbed, Protruding Head, Mechanically Locked Spindle
Special Features:	Single Action Installation; Utilizes Drive Anvil Washer As Part Of Rivet Assembly
Material:	Iron Alloy 660 Locking Ring
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Sleeve
Material Document And Classification:	Ams 5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring
Material Document And Classification:	Ams 5737 Assn Std 1st Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Aluminum Stem
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Nas4006 Assn Std Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S02AU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.