

**Description**

size: 1/8", grip range: 1/8" - 3/16", blind rivet (huck) - 100°, flush head - bulbed - general purpose - monel - for use with single action installation tool"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1921M04S03
Minimum Qty (MOQ):	25
NSN:	5320-01-099-4222
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N NAS1921M04S03 Specifications

<b>Fastener Length:</b>	0.323 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Special Features:</b>	Expander Material Iron Alloy Uns K66286 Ams 5737,locking Ring Material Iron Alloy Uns K66286 Ams 5737 Or Nickel Alloy Uns N04400 Qq-n-281,sleeve Material Nickel Alloy Uns N04400 Qq-n-281
<b>Surface Treatment:</b>	Passivate Expander Or Cadmium Expander
<b>Specification/standard Data:</b>	80205-nas1921 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.