



Military-Fasteners.com

P/N NAS1921M04S03

Description

size: 1/8", grip range: 1/8" - 3/16", blind rivet (huck) - 100°, flush head - bulbed - general purpose - monel - for use with single action installation tool"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921M04S03
Minimum Qty (MOQ):	25
NSN:	5320-01-099-4222
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1921M04S03 Specifications

Fastener Length:	0.323 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Special Features:	Expander Material Iron Alloy Uns K66286 Ams 5737,locking Ring Material Iron Alloy Uns K66286 Ams 5737 Or Nickel Alloy Uns N04400 Qq-n-281,sleeve Material Nickel Alloy Uns N04400 Qq-n-281
Surface Treatment:	Passivate Expander Or Cadmium Expander
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.