

**Description**

Fastener Length: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1921M04S03W   |
| Minimum Qty (MOQ): | 20 EA            |
| NSN:               | 5320-01-207-8627 |
| Schedule B:        | 7508.90.5000     |
| ECCN:              | EAR99            |



NO IMAGE  
AVAILABLE

## P/N NAS1921M04S03W Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.323 Inches Nominal   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                 |
| <b>Shank Diameter:</b>                                | 0.124 Inches Minimum And 0.128 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.221 Inches Minimum And 0.229 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.126 Inches Minimum And 0.187 Inches Maximum  |
| <b>Countersink Angle:</b>                             | 98.5 Degrees Minimum And 101.5 Degrees Maximum   |
| <b>Material:</b>                                      | Nickel Alloy Sleeve  |
| <b>Material:</b>                                      | Iron Alloy 660 Or Nickel Alloy Locking Ring  |
| <b>Material:</b>                                      | Iron Alloy 660 Stem  |
| <b>Material Document And Classification:</b>          | Ams5737 Assn Std 1st Material Response Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring |
| <b>Material Document And Classification:</b>          | Ams5737 Assn Std Single Material Response Stem   |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec Single Material Response Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Sleeve   |
| <b>Surface Treatment:</b>                             | Passivate Locking Ring   |
| <b>Surface Treatment:</b>                             | Passivate Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Locking Ring  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Sleeve                                   |
| <b>Specification/standard Data:</b>                   | 80205-nas1921 Professional/industrial Association Standard                                     |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S03W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.