

P/N NAS1921M04S03W

Military-Fasteners.com

#### Description

Fastener Length: 21/64"

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

| SKU / Model:       | NAS1921M04S03W   |
|--------------------|------------------|
| Minimum Qty (MOQ): | 20 EA            |
| NSN:               | 5320-01-207-8627 |
| Schedule B:        | 7508.90.5000     |
| ECCN:              | EAR99            |



# P/N NAS1921M04S03W Specifications

| Fastener Length:                               | 0.323 Inches Nominal   |
|--|--|
| Head Style:                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                 |
| Shank Diameter:                                | 0.124 Inches Minimum And 0.128 Inches Maximum  |
| Shank Style:                                   | Self-plugging Mechanically Locked Stem   |
| Head Major Diameter:                           | 0.221 Inches Minimum And 0.229 Inches Maximum  |
| Expansion Device:                              | Serrated Stem-type W   |
| Grip Length:                                   | 0.126 Inches Minimum And 0.187 Inches Maximum  |
| Countersink Angle:                             | 98.5 Degrees Minimum And 101.5 Degrees Maximum   |
| Material:                                      | Nickel Alloy Sleeve  |
| Material:                                      | Iron Alloy 660 Or Nickel Alloy Locking Ring  |
| Material:                                      | Iron Alloy 660 Stem  |
| Material Document And Classification:          | Ams5737 Assn Std 1st Material Response Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring |
| Material Document And Classification:          | Ams5737 Assn Std Single Material Response Stem   |
| Material Document And Classification:          | Qq-n-281 Fed Spec Single Material Response Sleeve  |
| Surface Treatment:                             | Cadmium Sleeve   |
| Surface Treatment:                             | Passivate Locking Ring   |
| Surface Treatment:                             | Passivate Stem   |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Locking Ring  |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem  |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Sleeve                                   |
| Specification/standard Data:                   | 80205-nas1921 Professional/industrial Association Standard                                     |

## **How to Order**

Order this rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S03W</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.