

## P/N NAS1921M04S04U

### **Description**

NAS1921M04S04U Blind Rivet

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1921M04S04U

Minimum Qty (MOQ): 10

NSN: 5320-01-508-9170

Schedule B: 7318.23.0000

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1921M04S04U Specifications

Fastener Length:	0.385 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Rq-4a
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Special Features:	Utilizes Drive Anvil Washer;requires Single Action Non-shifting Installation Tool
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Locking Ring Or Nickel Alloy Locking Ring
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Sleeve Or Aluminum Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416 Ty Ii, Cl 3 Fed Spec Single Treatment Response Sleeve Or Nas4006 Assn Std Single Treatment Response Sleeve

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S04U">https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S04U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S04U">https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S04U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S04U">https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S04U</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1921M04S04U">https://military-fasteners.com/rivets/NAS1921M04S04U</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1921M04S04U">https://military-fasteners.com/rivets/NAS1921M04S04U</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1921M04S04U">https://military-fasteners.com/rivets/NAS1921M04S04U</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1921M04S04U">https://military-fasteners.com/rivets/NAS1921M04S04U</a> and selecting the property of the property