

Description

Fastener Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M04S06W
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-211-7774
Schedule B:	7508.90.5000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1921M04S06W Specifications

Fastener Length:	0.510 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy Sleeve
Material:	Iron Alloy 660 Or Nickel Alloy Locking Ring
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams5737 Assn Std 1st Material Response Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M04S06W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.