

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921M0502W
Minimum Qty (MOQ):	10
NSN:	5320-00-080-0570
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N NAS1921M05-02W Specifications

Fastener Length:	0.263 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.080 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	2260 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy 400 Body
Material:	Nickel Alloy 400 Sleeve
Material Document And Classification:	Qq-n-281 Form 7 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-n-281 Form 7 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Specification/standard Data:	80205-nas1921 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05-02W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.