

Description

size: 5/32", grip range: 1/8" - 3/16", blind rivet (huck) - 100°, flush head - bulbed - general purpose - monel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921M0503
Minimum Qty (MOQ):	10
NSN:	5320-01-423-2521
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1921M05-03 Specifications

Fastener Length:	0.336 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Locking Ring
Material:	Nickel Alloy 400 Sleeve
Specification/standard Data:	80205-nas191921-05-03 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.