

P/N NAS1921M05-05PW

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1921M0505PW

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-068-2342

Schedule B: 7508.90.5000

ECCN: 9A991

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N NAS1921M05-05PW Specifications

Fastener Length:	0.461 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Rivet May Be Slosh Cleaned Before Installation
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1921M05-05PW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.