

**Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1921M0507PW
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-068-1338
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N NAS1921M05-07PW Specifications

<b>Fastener Length:</b>	0.586 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.376 Inches Minimum And 0.437 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Rivet May Be SlosH Cleaned Before Installation
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-b-281 Fed Spec All Material Responses Sleeve
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1921 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05-07PW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.