

**Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M0509
Minimum Qty (MOQ):	5
NSN:	5320-01-256-9762
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1921M05-09 Specifications

<b>Fastener Length:</b>	0.711 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.501 Nominal Mils And 0.562 Nominal Centimeters
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Copper Alloy Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem
<b>Specification/standard Data:</b>	80205-nas1921-05-09 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.