

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1921M0509
Minimum Qty (MOQ):	5
NSN:	5320-01-256-9762
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	096300, Rivets Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N NAS1921M05-09 Specifications

Fastener Length:	0.711 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Nominal Mils And 0.562 Nominal Centimeters
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Copper Alloy Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1921-05-09 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.