

P/N NAS1921M05S02

Military-Fasteners.com

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1921M05S02
Minimum Qty (MOQ):	25
NSN:	5320-01-240-8098
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N NAS1921M05S02 Specifications

0.263 Inches Nominal
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.155 Inches Minimum And 0.159 Inches Maximum
0.282 Inches Minimum And 0.290 Inches Maximum
Serrated Stem-type W
0.101 Inches Minimum And 0.125 Inches Maximum
1050 Pounds Per Square Inch
1565 Single Pounds Per Square Inch
98.5 Degrees Minimum And 101.5 Degrees Maximum
Single Action
Nickel Alloy Sleeve
Steel Corrosion Resisting Locking Ring Or Nickel Alloy Locking Ring
Steel Corrosion Resisting Stem
Ams5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring
Ams5737 Assn Std Single Material Response Stem
Qq-n-281 Fed Spec Single Material Response Sleeve
Cadmium Sleeve Or Aluminum Sleeve
Passivate Locking Ring
Passivate Stem
Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Qq-p-35 Fed Spec Single Treatment Response Stem
Qq-p-416,ty li,cl 3 Fed Spec Single Treatment Response Sleeve Or Nas4006 Assn Std Single Treatment Response Sleeve
80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S02</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.