

P/N NAS1921M05S03U

Military-Fasteners.com

Description

Fastener Length: 15/32"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1921M05S03U
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-508-7236
Schedule B:	7508.90.5000
ECCN:	EAR99



P/N NAS1921M05S03U Specifications

0.461 Inches Nominal
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.155 Inches Minimum And 0.159 Inches Maximum
0.282 Inches Minimum And 0.290 Inches Maximum
Serrated Stem-type W
Rivet, Blind
0.126 Inches Minimum And 0.187 Inches Maximum
98.5 Degrees Minimum
Single Action
Nickel Alloy Sleeve
Steel Corrosion Resisting Locking Ring Or Nickel Alloy Locking Ring
Steel Corrosion Resisting Stem
Ams 5737 Assn Std Single Material Response Stem
Ams5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring
Qq-n-281 Fed Spec Single Material Response Sleeve
Cadmium Sleeve Or Aluminum Sleeve
Passivate Locking Ring
Passivate Stem
Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Qq-p-35 Fed Spec Single Treatment Response Stem
Qq-p-416, Ty li Cl 3 Fed Spec Single Treatment Response Sleeve Or Nas4006 Assn Std Single Treatment Response Sleeve

How to Order

Order this rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S03U</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.