

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M05S04
Minimum Qty (MOQ):	10
NSN:	5320-01-240-8097
National Motor Freight:	095190, Hardware, Noi



NO IMAGE
AVAILABLE

P/N NAS1921M05S04 Specifications

Fastener Length:	0.388 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Minimum Tensile Strength:	1050 Pounds Per Square Inch
Shear Strength:	1565 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Special Features:	Single Action
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Locking Ring Or Nickel Alloy Locking Ring
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Sleeve Or Aluminum Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty li,cl 3 Fed Spec Single Treatment Response Sleeve Or Nas4006 Assn Std Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.