

**Description**

Fastener Length: 51/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M05S04AU
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-533-7542
Schedule B:	7318.23.0000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N NAS1921M05S04AU Specifications

<b>Fastener Length:</b>	0.788 Inches Minimum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.154 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Features Provided:</b>	Washer
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Body
<b>Material:</b>	Nickel Alloy 400 Locking Ring
<b>Material:</b>	Nickel Alloy 400 Sleeve
<b>Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response Body
<b>Material Document And Classification:</b>	Qq-n-281, Uns N04400 Fed Spec Single Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281. Uns N04400 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Aluminum Sleeve
<b>Surface Treatment Document And Classification:</b>	Nas4006 Assn Std Single Treatment Response Sleeve

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S04AU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.