

Description

Fastener Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M05S04AU
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-533-7542
Schedule B:	7318.23.0000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1921M05S04AU Specifications

Fastener Length:	0.788 Inches Minimum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.154 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Features Provided:	Washer
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Body
Material:	Nickel Alloy 400 Locking Ring
Material:	Nickel Alloy 400 Sleeve
Material Document And Classification:	Ams5737 Assn Std Single Material Response Body
Material Document And Classification:	Qq-n-281, Uns N04400 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-n-281. Uns N04400 Fed Spec Single Material Response Sleeve
Surface Treatment:	Aluminum Sleeve
Surface Treatment Document And Classification:	Nas4006 Assn Std Single Treatment Response Sleeve

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S04AU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.