

**Description**

Fastener Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1921M05S04U   |
| Minimum Qty (MOQ): | 15 EA            |
| NSN:               | 5320-01-508-2732 |
| Schedule B:        | 7508.90.5000     |
| ECCN:              | EAR99            |



NO IMAGE  
AVAILABLE

## P/N NAS1921M05S04U Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.398 Inches Nominal  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                                      |
| <b>Shank Diameter:</b>                                | 0.155 Inches Minimum And 0.159 Inches Maximum   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem  |
| <b>Head Major Diameter:</b>                           | 0.282 Inches Minimum And 0.290 Inches Maximum   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.188 Inches Minimum And 0.250 Inches Maximum   |
| <b>Countersink Angle:</b>                             | 98.5 Degrees Minimum And 101.5 Degrees Maximum  |
| <b>Special Features:</b>                              | Utilizes Drive Anvil Washer;requires Single Action Non-shifting Installation Tool                                   |
| <b>Material:</b>                                      | Nickel Alloy Sleeve   |
| <b>Material:</b>                                      | Steel Corrosion Resisting Locking Ring Or Nickel Alloy Locking Ring   |
| <b>Material:</b>                                      | Steel Corrosion Resisting Stem  |
| <b>Material Document And Classification:</b>          | Ams5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring         |
| <b>Material Document And Classification:</b>          | Ams5737 Assn Std Single Material Response Stem  |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec Single Material Response Sleeve   |
| <b>Surface Treatment:</b>                             | Cadmium Sleeve Or Aluminum Sleeve   |
| <b>Surface Treatment:</b>                             | Passivate Locking Ring  |
| <b>Surface Treatment:</b>                             | Passivate Stem  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Locking Ring   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty li, Cl 3 Fed Spec Single Treatment Response Sleeve Or Nas4006 Assn Std Single Treatment Response Sleeve |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S04U> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.