

Description

Flush countersunk head, self plugging, NAS1921 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | NAS1921M05S05 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-206-7393 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



P/N NAS1921M05S05 Specifications

| | |
|---|--|
| Fastener Length: | 0.461 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.290 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Special Features: | Single Action Installation; Color Yellow On Spindle |
| Material: | Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1921 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.