

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | NAS1921M05S06                                    |
| Minimum Qty (MOQ):      | 10 EA  |
| NSN:                    | 5320-01-206-7394                                 |
| Schedule B:             | 7508.90.5000                                     |
| ECCN:                   | EAR99  |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1921M05S06 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.523 Inches Maximum   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.155 Inches Minimum And 0.159 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.290 Inches Maximum   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.313 Inches Minimum And 0.375 Inches Maximum                                  |
| <b>Countersink Angle:</b>                             | 98.5 Degrees Minimum And 101.5 Degrees Maximum                                 |
| <b>Special Features:</b>                              | Single Action Installation; Color Yellow On Spindle                            |
| <b>Material:</b>                                      | Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve                           |
| <b>Material:</b>                                      | Iron Alloy 660 Stem  |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Stem                                |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec All Material Responses Sleeve                                |
| <b>Surface Treatment:</b>                             | Passivate Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem                                |
| <b>Specification/standard Data:</b>                   | 80205-nas1921 Professional/industrial Association Standard                     |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.