

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1921M05S07W |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-261-2449 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N NAS1921M05S07W Specifications

| | |
|--|--|
| Fastener Length: | 0.586 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.160 Inches Maximum |
| Head Major Diameter: | 0.282 Inches Minimum And 0.290 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.376 Inches Minimum And 0.437 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Nickel Alloy R-405 Sleeve |
| Material: | Iron Alloy 660 Expander |
| Material Document And Classification: | Ams5737 Assn Std Single Material Response Expander |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Sleeve |

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S07W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.