

Description

Fastener Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M05S08W
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-261-2450
Schedule B:	7508.90.5000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1921M05S08W Specifications

Fastener Length:	0.648 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy R-405 Sleeve
Material:	Iron Alloy 660 Expander
Material Document And Classification:	Ams5737 Assn Std Single Material Response Expander
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S08W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.