

**Description**

Fastener Length: 41/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M05S08W
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-261-2450
Schedule B:	7508.90.5000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N NAS1921M05S08W Specifications

<b>Fastener Length:</b>	0.648 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.160 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.438 Inches Minimum And 0.500 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy R-405 Sleeve
<b>Material:</b>	Iron Alloy 660 Expander
<b>Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response Expander
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S08W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.