

P/N NAS1921M05S08W

Description

Fastener Length: 41/64"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1921M05S08W

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-261-2450

Schedule B: 7508.90.5000

ECCN: EAR99



^{*} See page 2 for technical characteristics

P/N NAS1921M05S08W Specifications

Fastener Length:	0.648 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Self-plugging
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy R-405 Sleeve
Material:	Iron Alloy 660 Expander
Material Document And Classification:	Ams5737 Assn Std Single Material Response Expander
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S08W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S08W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S08W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/NAS1921M05S08W and selecting the quantity you want then