

## P/N NAS1921M05S09

### **Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1921M05S09

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-369-5785

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1921M05S09 Specifications

Fastener Length:	0.711 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Single Action, non-shifting Installation Tools, color Code Yellow On Spindle
Material:	Iron Alloy 660 Locking Ring Or Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ringnickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeveiron Alloy 660 Stem
Material Document And	Ams 5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring Or Qq-n-281 Fed Spec
Classification:	3rd Material Response Locking Ringqq-n-281 Fed Spec Single Material Response Sleeveams 5737 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

## **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S09">https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S09</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S09">https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S09</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S09">https://military-fasteners.com/rivets/blind+rivets/NAS1921M05S09</a> and selecting the quantity you want then