

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M0605
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-469-2399
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1921M06-05 Specifications

<b>Fastener Length:</b>	0.475 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy R-405 Locking Ring Or Nickel Alloy K-500 Locking Ring Or Iron Alloy 660 Locking Ring
<b>Material:</b>	Nickel Alloy R-405 Sleeve Or Nickel Alloy K-500 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring Or Ams 5737 Assn Std 3rd Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Sleeve

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.