

## P/N NAS1921M06-07

### **Description**

Fastener Length: 5/8", NAS1921 series rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1921M0607

Minimum Qty (MOQ):

NSN: 5320-01-027-6490

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









# P/N NAS1921M06-07 Specifications

Fastener Length:	0.600 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.189 Inches Minimum And 0.193 Inches Maximum
Shank Style:	Self-plugging Shank W/grooved End For Locking
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Locking Ring Or Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material Document And Classification:	Ams 5737 Assn Std 1st Material Response Locking Ring Or Qq-n-281 Fed Spec 2nd Material Response Locking Ring Or Qq-n-281 Fed Spec 3rd Material Response Locking Ring
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 For A286 Cres Oly Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-07">https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-07">https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-07">https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1921M06-07">https://military-fasteners.com/rivets/NAS1921M06-07</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1921M06-07">https://military-fasteners.com/rivets/NAS1921M06-07</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1921M06-07">https://military-fasteners.com/rivets/NAS1921M06-07</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1921M06-07">https://military-fasteners.com/rivets/NAS1921M06-07</a> and selecting the your cart you can check you can check