

# P/N NAS1921M06-09

## **Description**

Rivet part number

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1921M0609

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-469-7215

Schedule B: 7508.90.5000

ECCN: 9A991

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1921M06-09 Specifications

Fastener Length:	0.725 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.190 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Prowler Ea-6b Aircraft
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet, Blind,-general Purpose, Bulbed, 100 Degree Flush Head, Mechanically Locked Spindle
Special Features:	Locking Ring-passivate Per Qq-p-35 For Cres Only;intended For General Purpose Use In Both Thick Sheet Stack-up And In Thin Sheet Or Double Dimpled Applications;block 89 Upgrade
Material:	Nickel Alloy Sleeve
Material:	Iron Alloy 660 Locking Ring Or Nickel Alloy Locking Ring Or Steel Comp 316 Locking Ring
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams5737 Assn Std Single Material Response Locking Ring Or Qq-n-281 Fed Spec Single Material Response Locking Ring Or Ams5690 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Ams5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-282 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Sleeve Or Aluminum Sleeve
Surface Treatment:	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,type2,class3 Fed Spec Single Treatment Response Sleeve Or Nas4006 Assn Std Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

### **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-09">https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-09</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-09">https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-09</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-09">https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-09</a> and selecting the quantity you want then