

Description

NAS1921M06-12 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1921M0612
Minimum Qty (MOQ):	50
NSN:	5320-01-437-3268
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N NAS1921M06-12 Specifications

Fastener Length:	0.912 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.357 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Countersink Angle:	98.5 Degrees Nominal
Material:	Nickel Alloy K-500 Sleeve
Material:	Iron Alloy 660 Locking Ring
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Cadmium Locking Ring And Chromate Locking Ring
Surface Treatment:	Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 3 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1921M06-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.